

POWER CONTROL STATION X-SERIES COMMERCIAL

Item No.: 592.727



Actual product may vary

DESCRIPTION OF FUNCTIONS

The measuring equipment control cabinet for implementing the grid feed-in management system in your commercial PV power plant.

- Interface between the grid operator and your system
- blue'Logs, MX-Modules, energy meter and further components can be built in depending on the grid operator's requirements
- Cost-optimized all-in-one solution due to direct connection of communication lines
- Application area Indoor and Outdoor for moderate climate conditions

TECHNICAL DATA

Supply voltage:	100 V AC to 230 V AC / 16 A
Current consumption without ext. devices:	Max. 0.80 A
Protection class:	IP 66
UV resistant:	Yes
Operating temperature:	-15 °C to 45 °C
Dimensions (H x W x D):	600 x 500 x 230 mm
Weight:	17.0 kg
Installation:	Wall installation

INTERNAL POWER SUPPLY

Components:	Power supply unit 24 V DC ± 1 %, 2.5 A
Nominal input voltage range AC:	100 V AC to 240 V AC
Input voltage range AC:	85 V AC to 264 V AC
Efficiency:	> 90 % (for 230 V AC and nominal values)

Components:	UPS with integrated power storage 24 V DC, 2.5 A
Input voltage DC:	24 V DC
Capacity:	0.8 Ah
Efficiency:	> 95 % (Mains operation, with charged power storage)

CABLE SCREW CONNECTIONS

1 x M25 incl. splitted sealing insert (9 mm bis 17 mm / 4 mm bis 6 mm) for Ethernet
 1 x M20 (6 mm bis 13 mm) for Power supply
 7 x M16 (4,5 mm bis 10 mm) for Sensors

COMMUNICATION

Type:	RS485 Modbus / 2 wires Ethernet
-------	------------------------------------

EQUIPMENT

Power supply unit 24 V DC, 2.5 A

UPS with integrated power storage 24 V DC, 2.5 A, 0.8 Ah

Top-hat rail socket (optional)

- Socket extension GER (Item No.: 592.724 100)
- Socket extension UK (Item No.: 592.724 101)
- Socket extension ITA (Item No.: 592.724 102)
- Socket extension USA (Item No.: 592.724 103)
- Socket extension IN (Item No.: 592.724 104)
- Socket extension FR (Item No.: 592.724 105)
- Socket extension CH (Item No.: 592.724 106)

Prepared for:

- 1 blue'Log basic module (X-1000 / X-3000 / X-6000)
- Up to 4 extension modules (max. 2 MX-Module Multi I/O)
- 1 Transformer energy meter iEM3255 (3-phase, Modbus)
- 1 VPN LTE Router EBW-L100

If required, additional components can be implemented as a variant

SCHEMATIC DIAGRAMS

